



# 不等辺角管

UACJ押出加工の  
**アルミ合金押出材**  
 汎用押出材一覧表

製作区分	型番	形状寸法 (mm)					断面積 (mm <sup>2</sup> )	単位質量 (kg / m)	材質区分			
		A	B	T	R 1	R 2			I	II	III	IV
A	U 38017	30	25	1.5	-	-	156	0.421		○		
A	U 48015	40	30	2	1.5	-	262.1	0.708		○		
A	SJ 1038	80	40	3	0.5	-	683.8	1.846	○			
A	U 98006	150	25	2.5	-	-	850	2.295		○		
S	E9236	18	13	2.5	121.7	0.329	57	97		○		
S	39076	13	10	1.5	54.2	0.146	41	72		○		
S	39082	31.8	29.4	1.2	115.4	0.311	100	192		○		
S	39210	34	30	2	201.1	0.543	107	201		○		
S	39211	50	46	2	301.6	0.813	157	302		○		
S	39218	16	13	1.5	68.3	0.184	50	91		○		
S	39230	22	18	2	125.7	0.339	69	126		○		
S	39259	60.5	56.5	2	367.6	0.992	190	368		○		
S	39442	30	26	2	175.9	0.475	94	176		○		
S	39485	60	56	2	364.4	0.984	188	364		○		
S	39711	26.4	20.96	2.72	202.3	0.546	83	149		○		
S	39712	33.4	27	3.2	303.6	0.82	105	190		○		

- 角・平角
- 等辺アングル
- 不等辺アングル
- チャンネル
- I・H型
- 等辺角管
- 不等辺角管
- S形材
- T形材
- パイプ
- 六角